

IDEAL® ALL-PURPOSE 14" SEMI-RUGGED NOTEBOOK PC

The SA14S is a Semi-Rugged Notebook of a great versatility. It is designed for utilization in a wide range of field that demand toughness and durability, be it field service, public safety on military. The superior display functions of sunlight readable and night vision mode can adapt it to any illuminant. With a 14" HD LED display, Windows® 10 and Intel® 6th Generation Skylake-U CPU, it performs as a workstation and offers complete connectivity; SA14S represents an excellent value of full-function Semi-Rugged PCs.

### **RUGGED FEATURES**

SA14S is IP53 and MIL-STD 810G certified. It is built with high quality of magnesium alloy that guarantees to perform. It works at 15,000 feet in the air, extremely temperature of -20°C to +50°C, storage in -40°C to +71°C, or 26 drops from 3 feet.

# BACKLIT KEYBOARD

SA14S comes with optional waterproof backlit keyboard for ease of operation in low light condition.

#### **ADVANCED SECURITY**

- ∇ Computrace<sup>®</sup> Ready
- **▼ TPM 2.0**
- ∇ Quick Release HDD

## STEALTH MODE

Stealth Mode is needed in special mission such as stakeout operation. With a quick button, it immediately turns off all sounds and emitting lights while all programs remain running in the background.

# **ADVANCED DISPLAY**

SA14S is equipped with 14 inch TFT LCD (1366 x 768) with Anti-Glare Coating Glass to bring exceptional visual performance. With enhanced 500 nits brightness, SA14S provides excellent Sunlight Readable LCD display even under direct sunlight.Night Vision Mode is standard with Sunlight Readable LCD. It complies with NVIS Type I Class A for brightness and chromaticity.

### **Specifications**

Rugged Features	IP53 <sup>1</sup> Drop MIL-STD 810G 516.6 Procedure IV, 26 drops from 3 feet height onto plywood over concrete	Security	Smart Compu
	Vibration MIL-STD 810G 514.6 AnnexC Cat.4, Fig 514.6C-1 ASTM 4169-08 Truck Transport, 11.5.2 Random test , Assurance Level II Magnesium Alloy Chassis		Finger Kensin Stealth Quick
Environment	■ Temperature Operating: - 20°C ~ 50°C Storage: - 40°C ~ 71°C ■ Humidity Operating: 5% ~ 95% ■ Altitude	Keyboard & Buttons	Power RF ON
			<ul><li>Quick :</li><li>One Pi</li><li>One Si</li><li>Backlit</li></ul>
	Operating : 15,000 feet MIL-STD 810G 500.5 Procedure II Non Operating : 40,000 feet MIL-STD 810G 500.5 Procedure I	Expansion Slots	One Si
Operating System	■ Genuine Windows 10 Professional <sup>2</sup>		One E
CPU	■ Intel <sup>®</sup> 6th Generation Skylake-U	I/O Ports	Two U
Memory	■ Two DDRIIII sockets ( Max.32GB )		One es
Storage	■ 2.5" SATA HDD or SSD		One he
Multimedia Bay	■ DVD Super Multi		One R
Display	<ul> <li>14.0" HD( 1366 x 768 ) TFT LCD</li> <li>Resistive Touch Panel<sup>2</sup></li> <li>Sunlight Readable 500 nits Display<sup>2</sup></li> <li>Night Vision Mode<sup>4</sup></li> </ul>		One R One H One V One D
Audio	<ul> <li>Intel High Definition Audio</li> <li>1.5KHz Speaker x 1 / 90db</li> <li>Microphone x 2 for Mic. Array</li> </ul>	Battery	<ul><li>Dockin</li><li>Two R</li><li>Primar</li></ul>
Camera	■ 2.0 Mega-pixel Web - Cam	AC Adaptor	■ 100V -
Communication	<ul> <li>Two 10 / 100 / 1000 Mbps Ethernet</li> <li>Intel® Dual Band Wireless AC 8260(a/b/g/n/AC)</li> <li>Bluetooth 4.2</li> <li>LTE WWAN<sup>2</sup></li> <li>GPS<sup>2</sup> (UBLOX-NEO-M8N)</li> </ul>	Dimension	■ 342 mi
		Weight	■ 3.4 Kg ( with 9

Security	Smart Card Reader Computrace® Ready Intel®vPro TPM 2.0 Fingerprint Scanner Kensington Lock Stealth Mode Quick Release HDD	
Keyboard & Buttons	<ul> <li>Power ON / OFF button</li> <li>RF ON / OFF button</li> <li>Quick Setting Control button</li> <li>One Programmable button</li> <li>One Stealth or Night Vision Mode button</li> <li>Backlit Keyboard<sup>2</sup></li> </ul>	
Expansion Slots	<ul> <li>One SD card reader slot (SDHC)</li> <li>One Smart Card Reader</li> <li>One Express Card 54 slot<sup>2,5</sup>or PCMCIA type II</li> </ul>	
I/O Ports	<ul> <li>Two USB2.0</li> <li>One USB3.0</li> <li>One eSATA+USB3.0 Combo</li> <li>One headphone jack</li> <li>One microphone jack</li> <li>One RJ-45</li> <li>Second RJ-45<sup>2</sup></li> <li>One RS232 port</li> <li>One HDMI</li> <li>One VGA</li> <li>One DC-in</li> <li>Docking connector</li> <li>Two RF Pass-thru connectors for WWAN and GPS</li> </ul>	
Battery	Primary 9-Cells 7800 mAh battery pack: 8.5 hrs <sup>3</sup>	
AC Adaptor	■ 100V - 240V; 60W/90W	
Dimension	■ 342 mm (L) x 245 mm (W) x 47 mm (H)	
Weight	■ 3.4 Kg / 7.48 lbs <sup>3</sup> ( with 9-cell battery and 2.5" SATA HDD)	

- 1. Pass all function test after performing IP5x testing with Talcum Powder for 8 hrs
- 2. Optional items
- 3. Actual weight may vary with different configurations

- 4. Available with Sunlight Readable Display
- 5. Mutually exclusive with Express Card 54 and PCMCIA

#### Accessories







- Car Adapter
  - DC-In: 12V-24V, 65W
  - DC-Out: 19V
- Office Dock
- Vehicle Dock



