

PRODUCT DATASHEET FN14720_STELLA-FRESNEL

STELLA-FRESNEL

~25° beam for warehouse and outdoor lighting. Compatible with up to 30 mm LES size COBs.

TECHNICAL SPECIFICATIONS:

Dimensions Ø 90.0 mm

Height 23 mm

Fastening screw

Colour black

Box size 480 x 280 x 300 mm

Box weight 4 kg

Quantity in Box 80 pcs

ROHS compliant yes 10




MATERIAL SPECIFICATIONS:

Component	Туре	Material	Colour
STELLA-FRESNEL	Single lens	Silicone	clear
STELLA-FRAME	Holder	PA66	black



PRODUCT DATASHEET FN14720_STELLA-FRESNEL



PRODUCT DATASHEET FN14720_STELLA-FRESNEL


PHOTOMETRIC DATA (MEASURED):

CREE \$

LED CMA3090
FWHM 35.0°
Efficiency 88 %
Peak intensity 1.200 cd/lm

LEDs/each optic 1
Light colour White
Required components:






CREE 🕏

LED CXA/B 1816 & CXA/B 1820 & CXA 1850

FWHM 24.0° Efficiency 84 % Peak intensity 1.900 cd/lm

LEDs/each optic 1
Light colour White
Required components:






CREE ÷

LED CXA/B 1830 FWHM 26.0° Efficiency 85 % Peak intensity 1.600 cd/lm

LEDs/each optic 1 Light colour White Required components:

C14305 STELLA-CLAMP-CXA15-18






CREE \$

LED CXA/B 25xx
FWHM 32.0°
Efficiency 85 %
Peak intensity 1.200 cd/lm
LEDs/each optic 1

Light colour White Required components: Bender Wirth: 439 Typ L3





Published: 12/09/2018

PRODUCT DATASHEET FN14720_STELLA-FRESNEL

PHOTOMETRIC DATA (MEASURED):

