M700DM8-ME, 7-inch Rugged Tablet PC

A Rugged Tablet that Can Survive Any Environment and Get Real Work Done

M700DM8-ME is a compact rugged tablet PC with robust set of features designed to withstand industrial use while providing high tech solutions that increase productivity, improve safety, and reduce operational costs. The processing power comes from ARM's Cortex-A53 Octa Core processor that supports Android 7.0 OS. The tablet features a brilliant, in-plane switching with projective capacitive touch screen and offers 1280 x 720 pixel resolution. Weighing at just 1.2 pounds (approx. 550 grams) the M700DM8-ME delivers lightweight mobility in a pocket-size rugged tablet.



Highlights

- Cortex-A53 Octa Core Processor
- 7" 1280 x 720 TFT Panel with direct optical bonding
- Support Android 7.0 OS
- Hot-swappable battery design
- Default NFC Reader with optional 2D Barcode Reader
- IP65 waterproof and dustproof
- antimicrobial surface coating

Order Information			
M700DM8-ME	IE Default NFC Reader with optional 2D Barcode Read		
	Default 3G/4G LTE		

White color housing MOQ 500 PCS



M700DM8-ME, 7-inch Rugged Tablet PC

A Rugged Tablet that Can Survive Any Environment and Get Real Work Done

Display Specification		Mechanical and Enviro	onment	
Size Resolution Brightness	7-inch 1280 x 720 650 nit With direct optical bonding for sunlight readable	Dimension (W x L x H) Weight Housing Operating Temperature	212.4 x 132.8 x 19 mm (8.36 x 5.23 x 0.75 inches) ³ 550g Antimicrobial surface coating (Optional) 0°C to 35°C, Humidity up to 95%	
Touch Contrast Ratio Viewing Angle Technology	Multi-touch projected capacitive 800:1 80/80/80 • Ambient light sensor, g-sensor • Automatic screen rotation	Storage Temperature-20°C to 60°C, Humidity up to 95%Humidity5% to 95% RH, non-condensingIP ProofIP65 Certified, waterproof and dustproofShockMIL-STD-810G Method 516.6 Procedure IVibrationMIL-STD-810G Method 514.6 Procedure I		
System Specification		Drop	MIL-STD-810G Method 516.6, 5 ft to concrete ⁴	
Processor System Memory Storage Operating System	ARM [®] Cortex [™] -A53 Octa-core 1.3 GHz 2GB RAM [™] 16GB eMMC Additional storage available with optional Storage Card: SD (up to 2 GB), SDHC (up to 32 GB) Android 7.0	Power Management Power Input Battery Battery Operating Time Adapter	5V DC 3.7V 5300mAh Li-Poly optional for Hotswappable function 20Hr ⁵ 100-240V/ 5V 3A Adapter	
Wireless Communication		Accessories		
WLAN 802.11 a/b/g/n		Standard Accessories		
GPS WWAN	Bluetooth 4.0 Support BLE mode + wide-band speech GPS / AGPS / GLONASS 3G/4G LTE	Universal Adapter Battery Optional Accessories 6	9226015W05V1 98TZ00ZZ0001	
Interface	50/40 LTL	Battery Charging Dock	98TA00Z00003	
Docking Connector USB Power Input Micro SD SIM Card Slot Keyboard and Input Touch	1 x docking connector 1 x Micro USB OTG 1 x Power Jack 1 x Micro SD Card Slot 2 x SIM Card Slot 10-point multi touch,	Vehicle Dock (Charging + Connectors)98TA07Z00004Vehicle Dock (Charging Only)98TA07Z00003Desk Dock98TA07Z00005Hand Strap98K000A0004RCarry Bag9B00000000XMicro SD Card76G004300000Capacitive Touch Stylus9B0000000326Mobile Printer MX209B00000007BMobile Printer MX309B00000007A		
Button	support Hand / Gloves and Rain Mode On-screen QWERTY keyboard Button 1 x Volume +/- , 1 x Power Button, 1 x Home Button, 1 x Menu Button,	Vehicle Adapter Drawing 7	98TZ00ZZ0006	
LED Indicators	1 x Return Button, 1 x Trigger Button 2 x LED indicators (Power, Battery)			
Audio	· · · · · · · · · · · · · · · · · · ·			
Microphone Speaker Earphone	2 x Built-in Mic 1 x 1.2 W speaker 1 x Earphone			
Cameras				
Web Camera Rear Camera	2MP Camera 8MP Camera with LED auxilliary light (auto focus)			
Data Capture				
NFC Barcode	NFC (Read / Write, Peer to Peer mode) 2D Barcode Reader (Optional)	Do Not Expose	the Battery Pack to Excessive Heat, or Extreme Heat (Near Fire, in	
Security Function		Direct Sunlight for example) Do not expose bare skin to this product when handling this unit in extreme hot or		
Mobile Device Mgmt.	SOTI Mobicontrol compatible ²	Caution cold environme 1. Total usable memory will 2. SOTI are available upon re	be less depending upon actual system configuration	

- 2. SOTI are available upon request
- 3. Length measurements do not include protrusions.
- 4. The drop test with high-capacity battery must come with hand strap 5. Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.
- 6. Accessories and Integrated Options may vary depending on your configuration.
- 7. This is a simplified drawing and some components are not marked in detail.