


POSITION	A	B
6	12.96	5.08
8	15.50	7.62
10	18.04	10.16
12	20.58	12.70
14	23.12	15.24
16	25.66	17.78
20	30.74	22.86
24	35.82	27.94
26	38.36	30.48
28	40.96	33.02
30	43.44	35.56
34	48.52	40.64
40	56.14	48.26
50	68.84	60.96
60	81.54	73.66
64	86.62	78.74



RECOMMENDED P.C.B LAYOUT

SPECIFICATIONS

Material

Insulator : PBT, glass reinforced, rated UL 94V-0

Contact : Phosphor Bronze or Brass

Electrical

Current Rating : 1 Amp

Contact Resistance : 30 mΩ max.


Insulation Resistance : 3000 MΩ min.

Dielectric Withstanding Voltage : 500V AC for 1minute

Operating Temperature : -40°C to +105°C

◆ Terminated with L01-1.27mm pitch flat ribbon cable.

UNLESS OTHERWISE SPECIFIED
TOLERANCE
.X ±0.3
.XX ±0.2
.XXX ±0.1



DON CONNEX
ELE. CO., LTD

PART NAME:

DIP PLUG (.1" .1")

UNIT: mm

SCALE: / SHEET:1/1

DRAW NO. A11-01CAT-A

THIRD



FILE NO. A11-01CAT-A

RD

CHECK

2009/05/18