



**HOLE LAYOUT
(BOTTOM VIEW)**

SPECIFICATION:

1. CURRENT CARRYING CAPACITY : 1) AC: 100V 1A MAX.
2) DC: 12V 2A MAX.
2. CONTACT RESISTANCE : 30m OHM MAX.
3. INSULATION RESISTANCE : 50M OHM MIN. AT DC 250V
4. VOLTAGE WITHSTANCE : AC 250V 1 MINUTE.
5. INSERTION FORCE : 1.0KGS - 4.5KG
WITHDRAWAL FORCE : 0.8KGS - 3.0KG

ARRANGEMENT OF CONTACTS							4.	CONTACT TERMINAL	3~8	PBR-H 0.2t	SILVER PLATED			
							3.	EARTH TERMINAL	1	BRASS 0.3t	TIN			
NO OF CONTACTS	3	4	5	6	7	8	2.	COVER	1	P.B.T	BLACK COLOR	UL94V-0		
MODEL NO	MDC-323@	MDC-324@	MDC-325@	MDC-326@	MDC-327@	MDC-328@	1.	BODY	1	P.B.T	BLACK COLOR	UL94V-0		
HOLE LAYOUT							P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS		
							REVISION	APPROVAL BY	CHECKED BY	DRAWD BY	UNITS			
											ling	95.11.02		
											PROJECTION	PRODUCT	DRAWING NO.	SCALE
												MINI DIN SOCKET	MDC-323~328	5/1



UNITOP ELECTRONICS CO., LTD.