

Specifications
 Current Rating: 1Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 300V AC/DC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials
 Contact Material: Copper Alloy
 Insulation Material: Polyester, UL 94V-0
 Nylon-6T

All materials must be GP materials


Ordering Information

G PEA208 - XX XX A 01

No. of Pins per Row: 01=Tin, 02=Gold Flash, Duplex plating, 05=Gold Flash /Tin, ...

Contact Plating: 01=Tin, 02=Gold Flash, Duplex plating, 05=Gold Flash /Tin, ...

Recommended P.C.Board
 Hole Layout



REV.	01	UNIT	mm	SCALE	5:1		GENERAL TOLERANCE			DRAWN	LENGJIANUN	DATE	DWG. NO.	TITLE
							X. ± 5°	X. ± 1°	.X. ±	CHECK	DATE	G PEA208-A01	1.27 PIN HEADER	
							X. ± 2°	.X. ± 0.38		APPROVE	DATE	PART NO.	DUAL ROWS DIP TYPE	
							XXX. ± 0.5°	.XXX ± 0.25			DATE	G PEA208-XX XX A 01	BASE 1.00H	

格 菱 股 份 有 限 公 司
Greenconn Corporation