

Model Type	EBOX-3300A	EBOX-3300A-H	EBOX-3300A-M	EBOX-3300A-JSK	EBOX-3300A-L2	
	EBOX-3310A	EBOX-3310A-H	EBOX-3310A-M	EBOX-3310A-JSK	EBOX-3310A-L2	
Processor	Vortex86DX (600MHz)					
BIOS	AMI BIOS					
Memory	Onboard 256MB DDR2 for 3300A Series/ Onboard 512MB DDR2 for 3310A Series					
VGA	XGI Z9s with 32MB DDR2/ D-Sub 15-pin					
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)			LAN x 2		
USB (2.0)	External: 3 ports (Front x 2, Rear x 1)					
Audio	Mic in and Line out					
I/O	Micro SD	1x				
	Type I/II CF slot	1x				
	PS2	PS/2 for Keyboard/ Mouse x 1			N/A	
	RS-232	N/A		2x		
	Mini PCI Slot	N/A		1x	N/A	
IDE	1x					
Auto Power On	Yes					
Power	+5V @ 2A (10W)					
Dimensions	115 x 115 x 35 mm					
Unit Net Weight	520g					
Operation Temp.	5 ~ 50 °C					
Certifications	CE, FCC, VCCI					
Note	RS-232 COM ports in Full 9pin					

Features:

- High performance
- Fanless design
- VESA mounting support
- Vortex86DX (600MHz)
- Onboard 256MB/ 512MB DDR2
- PXE Diskless Boot
- IDE DOM support
- Compact Flash slot
- Micro SD slot
- 3 x USB V2.0 ports (2 at the front)
- 10/100 Mbps LAN
- 2 x RS-232 ports (Optional)
- Mini PCI socket (Optional)
- Wireless LAN (Optional)
- Ultra low power


DMP Electronics Inc.

No. 15, Wugong 5th Rd., New Taipei Industrial Park, New Taipei City 24890, Taiwan R.O.C

Tel: +886 2 2298 0770 Fax: +886 2 8990 1629