



RECOMMEND REAR MOUNT PANEL

RECOMMEND FRONT MOUNT PANEL

SPECIFICATIONS:

- .Insulator Material: PBT & G/F Reinforced, UL 94-V0
- .Contact Material: Phosphor bronze
- .Strain Relief Material: PBT & G/F Reinforced, UL 94-V0
- .Shell Material: Steel
- .Current rating : 1A : AWG28/1, 2A : AWG26
- .Insulation resistance : $\geq 1000 M \Omega$
- .Dielectric withstanding volatge : 500V, at sea level
- .Operating temperature : $-25^{\circ}C \sim +85^{\circ}C$ (limited by cable)
- .Contact resistance : $\leq 5m \Omega$
- .Wire size : AWG26 & AWG28 stranded, 1.27mm conductor center flat cable

73.95 (2.911)	70.90 (2.791)	68.50 (2.697)	73.75 (2.904)	51.84 (2.041)	74.85 (2.947)	82.80 (3.260)	50
58.85 (2.317)	53.75 (2.116)	51.50 (2.027)	58.65 (2.309)	36.72 (1.446)	59.74 (2.352)	67.80 (2.669)	36
45.88 (1.806)	37.50 (1.476)	35.50 (1.398)	45.68 (1.798)	23.76 (.935)	46.78 (1.842)	54.70 (2.154)	24
$\pm 0.25(.010)$	$\pm 0.25(.010)$	$\pm 0.25(.010)$	$\pm 0.20(.008)$	$\pm 0.13(.005)$	$\pm 0.13(.005)$	$\pm 0.25(.010)$	POS.

RoHS Compliant **HSM** 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 Betty		TOLERANCE 容許公差 .00 ± 0.25 .0 ± 0.38 ANGLE ± 1°	PART NAME 品名 CENTRONIC IDC TYPE PANEL TYPE METAL SHELL WITH S/R ROHS LOW-LEAD
DWG. 製圖 Betty	SCALE 比例 參考	SIZE. 紙張尺寸 A4	PART NO. 料號 C0714-XXFBYXX0R
DATE 制表日 2011/05/31	UNIT 單位 MM	REV. 版次 B	
	PAGE 張數 1 OF 1		