


# MANO882

LGA1150 Socket Intel® Xeon® E3-v3 and 4th Generation Intel® Core™ i7/i5/i3 & Celeron®, Pentium® Mini-ITX SBC with Intel® C226, HDMI/DisplayPort/VGA/LVDS, Dual LAN and USB 3.0

NEW



## System


CPU	LGA1150 Socket Intel® Xeon® E3-v3 and 4th Generation Intel® Core™ i7/i5/i3 & Celeron® and Pentium® processor (Haswell/ Haswell Refresh)
System Memory	2 x 204-pin SO-DIMM dual channel DDR3-1333/1600, max. up to 16 GB
Chipset	Intel® C226
BIOS	AMI
SSD	N/A
Watchdog Timer	255 level, 1 ~ 255 sec
Expansion Interface	1 x PCIe x16 Gen3 1 x PCI Express mini card (Full size and shared mSATA) 1 x SIM card slot
Battery	Lithium 3V/220 mAH
Power Requirements	Intel® i7-4770S +5V@2.62A, +12V@4.97A, +5VSB@0.04A, +3.3V@0.76A
Size/Weight	170 x 170 mm
Temperature	0°C ~ +60°C (32°F ~ 140°F), operation
Operation Humidity	10% ~ 95% relative humidity, non-condensing

## I/O

MIO	1 x PS/2 KB & MS 2 x RS-232/422/485 (COM 1-2, on rear IO) 4 x RS-232 (COM3-6; by pin header); COM1, 2 with 5V/12V power
SATA	4 x SATA-600 Support RAID 0/1/5/10 (Optional: Intel® H81: 2 x SATA 600)
Hardware Monitoring	Detect CPU/System temperature, voltage and fan speed, smart fan supported.
Ethernet	1st port as 10/100/1000 Mbps supports WOL, PXE with Intel® i217LM (LAN1) 2nd port as 10/100/1000 Mbps supports WOL, PXE with Intel® i210AT (LAN2)
Audio	HD Audio as Mic-in/Line-out with Realtek ALC662
USB	C226: 4 x USB 3.0 (2 on Rear IO, 2 on internal) 6 x USB 2.0 (2 on Rear IO, 4 on internal) H81: 2 x USB 3.0 (2 on Rear IO) 6 x USB 2.0 (2 on Rear IO, 4 on internal)
TPM	Infineon TPM 1.2 SLB9635 (Intel® C226)
Digital I/O	8 Channels Programmable (4-IN & 4-OUT default)
SM BUS	N/A

## Features

- LGA1150 Socket Intel® Xeon E3-v3 and 4th Generation Intel® Core™ i7/i5/i3 & Celeron® & Pentium® processor (Haswell/ Haswell Refresh)
- 2 DDR3-1333/1600 MHz, max. up to 16 GB
- PCIe x16 Gen3 supported
- 4 SATA-600 with RAID 0,1, 5 and 10
- mSATA and SIM slots supported
- Intel® AMT 9.0 supported (Intel® C226)
- TPM 1.2 supported
- Triple view display (DP is a must to support triple view)



▲ Side view

## Display

Chipset	Intel® HD 4000/ 5000 Graphics
Memory Size	Shared Memory
Display Interface	1 x HDMI (Intel® C226) 1 x DP 1 x VGA 1 x LVDS 24 bit dual channel

## Packing List

<b>Standard</b>	I/O Bracket, Driver CD, COM & SATA Cable
-----------------	--

## Ordering Information

<b>Standard</b>	
MANO882	LGA1150 Socket Intel® Xeon® E3-v3 and 4th Generation Core™ i7/i5/i3, Pentium®, Celeron® (Haswell/ Haswell Refresh) Mini-ITX SBC with Intel® C226 Chipset, HDMI/ DisplayPort/ VGA/ LVDS, Dual GbE LAN and USB 3.0
<b>Optional</b>	
MANO882-H81	LGA1150 Socket Intel® 4th Generation Core™ i7/i5/i3, Celeron® and Pentium® (Haswell/ Haswell Refresh) Mini-ITX SBC with Intel® H81 Chipset, DisplayPort/ VGA/ LVDS, Dual GbE LAN and USB 3.0