

AX61133TM

1U Dual Hot swapping SATA HDD Tray
Rackmount classis for ATX Motherboard



Supports 2 x 3.5" hot-swappable SATA HDD tray
Easy-to-maintain tray design

Features

- Supports 12" x 9.6" standard ATX Motherboard
- Supports two 3.5" SATA HDD (hot-swappable tray)
- Supports one PCI or PCIe riser card
- Supports ATX 270W power supply



▲ Front view



▲ Rear view



DDR3

Specifications

Standard Color	Black
Construction	Heavy-duty steel
Drive Capacity	Exposed 2 x SATA HDD drive bay (hot swappable tray)
Cooling	2 x 4 cm ball bearing fans (15.3 CFM/each)
Front Panel Indicators	1 x power on/off, 1 x HDD
Front Panel Controls	1 x power on/off
Front Panel Connectors	N/A
Pre-punched Panel	N/A
System Board	IMB206/IMB207/IMB208

Expansion Interface	1 x PCI slot (32 bits/33 MHz) or 1 x PCIe slot
Operating Temperature	0°C ~ +40°C (+32°F ~ +104°F)
Dimensions	473.5 mm (19") (W) x 440 mm (17.32") (D) x 44 mm (1.73") (H)
Weight (net/gross)	9.8 kg (21.6 lb)/10.8 kg (23.8 lb)

Power Supply Specifications

Items	Watt	Input	Specifications	MTBF
			Output	
PS270-1U	ATX 270W (PFC)	AC 90-264V (Auto)	+5V @ 18A	100,000 hours
			+12V 1 @ 16A	
			+12V 2 @ 10A	
			+3.3V @ 16A	
			-12V @ 0.8A	
+5VSB @ 2.5A				

Ordering Information

AX61133TM/X270	With ATX270W Power supply, PCI version
AX61133TM/X270	With ATX270W Power supply, PCIe version

*Specifications and certifications are based on options and may vary.

Recommended MB Selections

IMB206 with LGA1156 heatsink (manufacture option)
 IMB207 with LGA1156 heatsink (manufacture option)
 IMB208 with LGA1156 heatsink (manufacture option)

Optional Items

E296200100	AX96200 1-slot 32-bit PCI riser card
84306113300E	PCIe x16 riser card L: 3250 mm
50761133100E	LGA1156 1U passive CPU cooler

Dimensions

