



BAT54W/AW/CW/SW

FEATURES


- Extremely Fast Switching Speed
- Low forward voltage




BAT54W




BAT54AW



BAT54CW



BAT54SW






MAXIMUM RATINGS ($T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Peak Repetitive Reverse Voltage	V_{RRM}		
Working Peak Reverse Voltage	V_{RWM}	30	V
DC Blocking Voltage	V_R		
Forward Continuous Current	I_{FM}	200	mA
Non-repetitive Peak Forward Surge Current @ $t < 1\text{s}$	I_{FSM}	600	mA
Repetitive Peak Forward Current @ $t \leq 1\text{s}, \delta \leq 0.5$	I_{FRM}	300	mA
Power Dissipation	P_D	200	mW
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	500	°C/W
Junction Temperature	T_J	125	°C
Storage Temperature	T_{stg}	-55~+150	°C

ELECTRICAL CHARACTERISTICS($T_a=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse voltage	$V_{(BR)}$	$I_R=100\mu\text{A}$	30			V
Reverse current	I_R	$V_R=25\text{V}$			2	μA
Forward voltage	V_F	$I_F1=0.1\text{mA}$			0.24	V
		$I_F2=1\text{mA}$			0.32	V
		$I_F3=10\text{mA}$			0.40	V
		$I_F4=30\text{mA}$			0.50	V
		$I_F5=100\text{mA}$			1	V
Diode capacitance	C_D	$V_R=0\text{V}, f=1\text{MHz}$			10	pF
Reverse recovery time	t_{rr}	$IF=IR=10\text{mA}$ $IrR=0.1 \times IR, RL=100\Omega$			5	ns

BAT54W/AW/CW/SW

Forward Characteristics

Reverse Characteristics

Capacitance Characteristics

Power Derating Curve
