



PCB板开孔尺寸
PCB LAYOUT

技术参数/Specifications	
额定参数/Rating	0.3A 50V DC
环境温度/Environment Temperature	-25°C ~ 70°C
接触电阻 Contact Resistance	≤ 50mΩ
绝缘电阻/Insulation Resistance	≥ 5MΩ (at 500VDC)
耐电压 Terminal-Insulation Voltage	100V AC/1min
针脚-外壳 Terminal-Body	500V AC/1min
机械寿命 Mechanical life	插入/选择各2000次 insert/select each 2000 Cycles

NOTE:
TOLERANCE UNLESS OTHERWISE SPECIFIED
X. ± 0.30 . X ± 0.20 . XX ± 0.15

修改日期/修改记录 MODIFY DATE/REVISION	
由谁/谁 BY/WHO	
日期 DATE	

成品图 Product Drawing DC-0053		浙江佳龙电子有限公司 ZHEJIANG JIALONG ELECTRON CO., LTD	
设计 DESIGN	杨渝 YANG YU	审核 CHECK	刘敏 LIU MIN
制图 DRAWING	杨渝 YANG YU	审核 CHECK	刘敏 LIU MIN
日期 DATE	Dec-11-2015	日期 DATE	
投影 PROJECTION	第一角 1st ANGLE	版次 REV.	A0
比例 SCALE	3:1 (A4)	重量 WT.	
共1页 THE 1 PAGE		第1页 PAGE 1	
DC插座 DC Power Socket		101-DC-0053	